



Equipment

# CC BOX

DECODER

With the **EiTV CC Box**, the broadcaster can use the digital distribution link or the VHF / UHF signal from the Digital Transmitter to provide the signal to the Analog Transmitter, simplifying the operation completely.



**It allows the insertion of the information of disconnection of the analog transmission, published in the Brazilian ordinance nº 378, of January 22, 2016.**

The inserts of Logo, Text in Crawl and Cartela can be done both manually and automatically!

**EiTV CC Box** is a set-top box developed for contribution systems that are using IP networks for the transmission of ISDB-Tb data, with support for TSoVerUDP or TSoVerRTP formats and 188 or 204 bytes (BTS) packets. The equipment will decode one of the services present in the flow, according to the configuration.

**EiTV CC Box** can also be used to directly tune the ISDB-Tb (VHF / UHF) digital signal of the broadcaster.

The Closed Caption conversion module, is responsible for decoding the received text in ARIB-824 protocol and convert it to the **CEA-608** standard that will be inserted in Field 1 of Line 21 in composite output.

This content can also be inserted into a SD/HD-SDI signal through an external Closed Caption inserter through TCP/IP communication.



**EiTV CC Box** decoder has the ability to decode the ISDB-Tb signal and generate the composite format (NTSC / PAL-M) with the caption on line 21 and apply the LetterBox / PanScan video formats.

It also has automatic switching between the RF and IP inputs (Main / Backup) and TSoVerUDP streaming when the content is received by the RF tuner.

## TECHNICAL SPECIFICATIONS

### Video Decoding:

- Standard: H.264 (MPEG-4 AVC), MPEG2
- Format: 480i, 720p and 1080i
- Frame Rate: 25, 30, 50 and 60 fps
- Video frequency: 50 and 60Hz

### Audio Decoding:

- Standard: HE-AAC@L4, AAC e MPEG1

### Management:

- Interface WEB
- SNMP

### Input Interfaces:

- Tuner ISDB-T: VHF / UHF Frequency Range 174 to 806 MHz (channels 7 to 69)
- Ethernet RJ45 (100 Mbps): TSoVerUDP, TSoVerRTP (188/204 bytes per packet)

### Output Interfaces:

- HDMI
- Composite Video (PAL-M and NTSC) and Stereo Audio (Left / Right)
- Ethernet RJ45 (100 Mbps): TSoVerUDP (188 bytes)



**EiTV – Entretenimento e Interatividade para TV Digital**  
Rua Rafael Andrade Duarte, 600 – 6º Andar  
Jardim Paraíso - CEP 13.100-011 - Campinas - SP - Brasil  
Fone/Fax: (19) 3579-0744  
E-mail: atendimento@eitv.com.br  
WEB Site: [www.eitv.com.br](http://www.eitv.com.br)